



# THE PREMIER RANGE

VarioQool Inverter Series

For maximum efficiency, you need a good night's sleep. And for the best sleep, you need an efficient air conditioner that cools your surroundings equally, maintains absolute silence and so that you don't lose sleep over electricity bills, also saves power.

### Vario QOOL™

The 5th-gen VarioQool technology features a Tropical-X Rotary compressor and full BLDC motor technology with enhanced airflow efficiency that offers ultra quiet performance for the perfect sleep.



AI 4-in-1 convertible cooling that adjusts cooling capacity as per the ambient room conditions for 25% faster cooling and upto 40% energy savings (in eco mode) versus conventional ACs.



#### SPLIT INVERTER SERIES

# VARIOQOOL 5G



#### THE CEO'S CHOICE.

Designed to adorn the walls of high-class living spaces for precise climate control, so that you can concentrate on pushing the limits.



## SMART MODES

This remote features a 4-way Auto swing and Convertible Cool modes for faster cooling.



#### HD OUTDOOR UNIT

Boasts a 100% copper condenser with Rust-O-Shield Nano paint protection.

MODEL		CWCDFK-VQ5G183	CWCVFJ-VQ5G243
BEE Star Rating		3	3
Cooling Capacity	Ton	1.5	2.0
(100% / 50% Load)	W	5000/ 2514	6350/ 3241
Convertible Capacity (H/L)	W	2500/ 5475	2550/ 6350
Power Consumption	W	1520/ 556	1965/ 752
Current Input	Α	7.6	9.2
ISEER	W/W	3.90	3.94
INDOOR UNIT			
Panel/ Strip Colour		Matt White/ Gold	Matt White/ Gold
Airflow Volume (H/L)	m3/h	800	1050
Fan Speed (H/L)	rpm	1250/850	1200/850
Noise Level (H/L)	dB (A)	35	40
Net Dimensions (WxDxH)	mm	900x206x294	1010x220x315
Gross Weight	kg	13.0	16.0
OUTDOOR UNIT			
Compressor/ Condensor	type	Inverter/ Copper	Inverter/ Copper
Refrigerant Type/ Charge	type	R32/ 0.480	R32/ 0.740
Net Dimensions (WxDxH)	mm	780x290x605	780x290x605
Gross Weight	kg	31	34
Piping Conx: Liquid/ Gas	Dia	φ6.35 / φ12.7	φ6.35 / φ12.7
Ambient Operating Range	°C	55	55
PREMIUM FEATURES			
Indoor Unit Display Type		Magic LED	Magic LED
Airflow Control Type		4 Way Auto	4 Way Auto
Remote Control		Wireless Backlit	Wireless Backlit
BLDC Technology		Yes (ODU)	-
Electronic EEV		-	-
<b>Evaporator Protection</b>		Gold-tec	Gold-tec
Condenser Protection		Gold-tec	Gold-tec
Rust-O-Shield Protection		Yes (IDU side)	Yes (IDU side)
Express Cool 55°C		Yes	Yes
Aurasense (IFEEL)		Yes	Yes
PM2.5 Filter		-	-
HD Dust Filter		Yes	Yes

(100% / 50% Load) Convertible Capacity (H/L) Power Consumption Current Input ISEER	W W W A	5000/ 2514 2500/ 5475 1520/ 556 7.6 3.90	2.0 6350/ 3241 2550/ 6350 1965/ 752 9.2 3.94
INDOOR UNIT Panel/ Strip Colour Airflow Volume (H/L) Fan Speed (H/L) Noise Level (H/L) Net Dimensions (WxDxH) Gross Weight	m3/h rpm dB (A) mm kg	Matt White/ Gold 800 1250/850 35 900x206x294 13.0	Matt White/ Gold 1050 1200/850 40 1010x220x315 16.0
OUTDOOR UNIT Compressor/ Condensor Refrigerant Type/ Charge Net Dimensions (WxDxH) Gross Weight Piping Conx: Liquid/ Gas Ambient Operating Range	type type mm kg Dia °C	Inverter/ Copper R32/ 0.480 780x290x605 31 \phi6.35 / \phi12.7	Inverter/ Copper R32/ 0.740 780x290x605 34 φ6.35 / φ12.7
PREMIUM FEATURES Indoor Unit Display Type Airflow Control Type Remote Control BLDC Technology Electronic EEV Evaporator Protection Condenser Protection Rust-O-Shield Protection Express Cool 55°C Aurasense (IFEEL) PM2.5 Filter HD Dust Filter Auto Blow-n-Clean		Magic LED 4 Way Auto Wireless Backlit Yes (ODU) - Gold-tec Gold-tec Yes (IDU side) Yes Yes - Yes Yes	Magic LED 4 Way Auto Wireless Backlit Gold-tec Gold-tec Yes (IDU side) Yes Yes - Yes

TONNAGE CLASS 1.5 2.0 3☆ 3☆ STAR RATING

### LUXURY FEATURES



















<sup>\*</sup>Under standard test conditions. As part of continuous research and development at Cruise, the above features, specifications and models may change without prior notice. Product images shown are for reference only. Actual features may vary. #Area of cooling is subject to outdoor ambient temperature of 35°C and calculated for residential purposes only.