



TURBOSTATION 300

TurboStation 300 is engineered for power play. Turbo Cool blows cool air uniformly and steadily. Sweeps in comfort even at 50°C while 4D Auto Airflo ensures you feel the cool wind in every corner.

THE MAXIAIR RANGE

TurboStation Non-Inverter Series

Performance meets perfection. A collective of tall, sleek cooling products to take your ideas and business to the next level. Designed for Glamorous Living Rooms, Large Workspaces, Café's & Restaurants and Convention Centres.



Tropical-X Scroll Compressor



4D Auto Airflo



Tropical-X Rotary Compressor (2.0T only)



50ft Air-throw



Dust Filter



Express Cool 50° C



3-Phase Advantage



Auto Blow-n-Clean

TONNAGE CLASS	2.0	3.0	4.0	5.0
---------------	-----	-----	-----	-----

STAR RATING	2*	-	-	-
-------------	----	---	---	---

PRODUCT TYPE
SERIES

FLOOR STANDING TYPE
TURBOSTATION



MODEL		CFFKCD-TS324CS	CFFKCD-TS336CS	CFFKCD-TS348CS	CFFKMD-TS360MS
Nominal Cooling Capacity	Tonnage	2.0	3.0	4.0	5.0
	Btu/hr	24000	36000	48000	60000
Power Consumption	W	2780	3870	5100	6000
Rated Current	A	12	6.1	8	11
EER	W/W	2.74	2.73	2.72	2.93
BEE Star Rating		2	-	-	-
INDOOR UNIT					
Panel/Colour	V/ Hz/ Ph	White	White	White	White
Power Supply	m3/h	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1
Airflow Volume (H/L)	rpm	1100	1800	1800	2500
Fan Speed (H/L)	dB (A)	440/270	500/400	500/400	615/530
Noise Level (H/L)	mm	47	54	54	59
Unit Dimensions (WxDxH)	mm	480x230x1652	600x313x1868	600x313x1868	610x390x1925
Net/ Gross Weight (Unit)	Kg	38/49	57/63	57/63	58.5/78.3
OUTDOOR UNIT					
Power Supply	V/ Hz/ Ph	220-240/50/1	380-415/50/3	380-415/50/3	380-415/50/3
Condensor Type		Copper	Copper	Copper	Copper
Compressor Type		Rotary	Scroll	Scroll	Scroll
Sound Pressure Level	dB (A)	55	67	67	68
Refrigerant Type/ Charge	Type/ Kg	R 32/1.1	R 22/2.4	R 22/3.2	R 22/4.0
Ambient Operation Range (max)	°C	48°C	48°C	48°C	48°C
Dimensions (WxDxH)	mm	895x368x650	1040x440x695	1040x440x695	1040x440x745
Net/ Gross Weight	Kg	43/48	78/96	81/99	85/103
Piping Connection: Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ12.17
Piping Connection: Gas	mm	Φ16	Φ19	Φ19	Φ19
PREMIUM FEATURES					
Indoor Unit Display Type		Digital	Digital	Digital	Digital
Airflow Control Type		4 Way	4 Way	4 Way	4 Way
Remote Control		Wireless LED	Wireless LED	Wireless LED	Wireless LED
Condensor Protection		Gold-tec	Blue-tec	Blue-tec	Blue-tec
AURASense Intelligence		-	-	-	-
Express Cool 50°C		Yes	Yes	Yes	Yes
Dust Filter		Yes	Yes	Yes	Yes
Auto Smart Check		Yes	Yes	Yes	Yes
Auto Blow-n-Clean		Yes	Yes	Yes	Yes

*Under Standard Test conditions. As part of continuous research and development at Cruise, the above features, specifications and models may change without prior notice. Product images shown are for reference only, actual features may vary.
 **Area of cooling is subject to outdoor ambient temperature of 35°C and calculated for residential purpose only.