



VARIOQOOL 3G | 3D

The VarioQool 3G and VarioQool 3D air conditioner with its Armani gold halo emnates superiority. Equipped with 2-way and 4-Way Auto Airflow, a 7-stage air purification system and Cruise's 5th gen Tropical Inverter technology - it is engineered to keep your environment fresh, cool and comfortable all day long. Blue-tec fins with Rust-O-Shield protection ensures rust-free performance for years to come.



THE PREMIER RANGE

VarioQool Inverter Series

For maximum efficiency, you need a good night's sleep. And for the best sleep, you need an efficient air conditioner that cools your surroundings equally, maintains absolute silence and so that you don't lose sleep over electricity bills, also saves power.

VarioQOOL[™]

The 5th-gen VarioQool technology features a Tropical-X Rotary compressor and full BLDC motor technology with enhanced airflow efficiency that offers ultra quiet performance for the perfect sleep.



AI 4-in-1 convertible cooling that adjusts cooling capacity as per the ambient room conditions for 25% faster cooling and upto 40% energy savings (in eco mode) versus conventional ACs.

Cruise

SPLIT INVERTER SERIES

VARIOQOOL 3G | 3D



THE CEO'S CHOICE.

Designed to adorn the walls of high-class living spaces for precise climate control, so that you can concentrate on pushing the limits.



SMART MODES


This remote features a 4-way Auto swing and Convertible Cool modes for faster cooling.



HD OUTDOOR UNIT

Boasts a 100% copper condenser with Rust-O-Shield Nano paint protection.

| MODEL | | CWCVBK-VQ3G183 | CWCVBK-VQ3G185 | CWCVBK-VQ3D183 | CWCVBK-VQ3D185 |
|----------------------------|----------|------------------|------------------|------------------|------------------|
| BEE Star Rating | | 3 | 5 | 3 | 5 |
| Cooling Capacity | Ton | 1.5 | 1.5 | 1.5 | 1.5 |
| (100% / 50% Load) | W | 5050/ 2530 | 4650/ 2350 | 5050/ 2530 | 4650/ 2350 |
| Convertible Capacity (H/L) | w | 5300/ 3030 | 4880/ 2790 | 5300/ 3030 | 4880/ 2790 |
| Power Consumption | w | 1620/ 610 | 1150/ 430 | 1620/ 610 | 1150/430 |
| Current Input | A | 8.0 | 5.4 | 8.0 | 5.4 |
| ISEER | A W/W | 3.90 | 5.10 | 3.90 | 5.4 |
| ISEEK | VV/VV | 3.90 | 5.10 | 3.90 | 5.10 |
| INDOOR UNIT | | | | | |
| Panel/ Strip Colour | | Matt White/ Gold | Matt White/ Gold | Matt White | Matt White |
| Airflow Volume (H/L) | m3/h | 900 | 900 | 900 | 900 |
| Fan Speed (H/L) | rpm | 1050/ 950 | 1050/ 950 | 1050/ 950 | 1050/ 950 |
| Noise Level (H/L) | dB (A) | 49/ 43 | 49/ 43 | 49/ 43 | 49/ 43 |
| Net Dimensions (WxDxH) | mm | 904x295x230 | 904x295x230 | 904x295x230 | 904x295x230 |
| Gross Weight | kg | 12.0 | 12.0 | 12.0 | 12.0 |
| OUTDOOR UNIT | | | | | |
| Compressor/ Condensor | type | Inverter/ Copper | Inverter/ Copper | Inverter/ Copper | Inverter/ Copper |
| Refrigerant Type/ Charge | type | R32 | R32 | R32 | R32 |
| Net Dimensions (WxDxH) | mm | 781x557x241 | 781x557x281 | 781x557x241 | 781x557x281 |
| Gross Weight | kg | 28.5 | 31 | 28.5 | 31 |
| Piping Conx: Liquid/ Gas | Dia | φ6.35/ φ12.7 | φ6.35/ φ12.7 | φ6.35/ φ12.7 | φ6.35/ φ12.7 |
| Ambient Operating Range | °C | 50 | 50 | 50 | 50 |
| PREMIUM FEATURES | | | | | |
| Indoor Unit Display Type | | Magic LED | Magic LED | Magic LED | Magic LED |
| Airflow Control Type | | 4 Way Auto | 4 Way Auto | 2 Way Auto | 2 Way Auto |
| Remote Control | | Wireless Backlit | Wireless Backlit | Wireless Backlit | Wireless Backlit |
| BLDC Technology | | Yes | Full BLDC | Yes | Full BLDC |
| Electronic EEV | | - | Yes | - | Yes |
| Evaporator Protection | | Blue-tec | Blue-tec | Blue-tec | Blue-tec |
| Condenser Protection | | Blue-tec | Blue-tec | Blue-tec | Blue-tec |
| Rust-O-Shield Protection | | Yes (IDU side) | Yes (IDU side) | Yes (IDU side) | Yes (IDU side) |
| Express Cool 50°C | | Yes | Yes | Yes | Yes |
| 7 Stage Air Purification | | Yes | Yes | Yes | Yes |
| PM2.5 Filter | | Yes | Yes | Yes | Yes |
| HD Dust Filter | | Yes | Yes | Yes | Yes |
| Auto Blow-n-Clean | | Yes | Yes | Yes | Yes |



LUXURY FEATURES





LIFETIME WARRANTY



24 LARGE DISPLAY

2D

AUTO SWING









*Under standard test conditions. As part of continuous research and development at Cruise, the above features, specifications and models may change without prior notice. Product images shown are for reference only. Actual features may vary. #Area of cooling is subject to outdoor ambient temperature of 35°C and calculated for residential purposes only.