

The Cruise logo is displayed in white, italicized sans-serif font on a solid blue rectangular background in the top right corner.

Cruise



FLOOR STANDING AIR CONDITIONERS

Cruise TurboStation Floor Standing air conditioners are perfect for transforming any large commercial space into a haven of comfort and elegance. Available in multiple cooling capacities featuring up to 60 ft FlusoJet airflow that allows your guests to stay in comfort without the hassle of complex wall installations of conventional AC units.





FLOOR STANDING AIR CONDITIONERS

Cruise's new Floor Standing Tower ACs blend style and functionality seamlessly. Ideal for offices, restaurants, showrooms & ballrooms with their ability to enhance any décor with powerful performance.



PREMIUM FEATURES

-  Luxury Sturdy Design
-  Upto 50feet Air Throw
-  Active Air Purification
-  2D/ 4D Auto Air Swing
-  Ultra-Quiet Operation
-  Flexible Installation
-  LED Display on Unit
-  Ultra Durable & Easy Cleaning
-  Express Cool 52°C
-  InfernoPac ODU Design

Technical Specifications

MODEL (SET) Indoor Unit Outdoor Unit	CFCDBK-TS536S1 CFFDBK-TS536SS1 CFODBK-TS536SS1	CFCDBK-TS548ST1 CFFDBK-TS548ST1 CFODBK-TS548ST1	CFFKMG-TS36ONS - -
Performance Parameters			
Model Type	Non-Inverter	Non-Inverter	Non-Inverter
Tonnage Class	3.0	4.0	5.0
BEE Star Rating	1	1	-
Cooling Capacity	10600	12700	17500
Power Consumption	3500	4580	7000
Current Input	15.98	11.60	13.00
ISEER	3.03	2.77	-
Indoor Unit			
Power Supply/ Via	V/Hz/Ph	230/50/1	230/50/1
Airflow Volume (H)	m³/h	1800	2280
Motor Type	BLDC	BLDC	AC
Noise Level (H/L)	dbA	52/ 46	53/ 49
Unit Dimensions (WxDxH)	mm	600x386x1850	600x386x1850
Net/ Gross Weight	kg	57/ 69	59/ 71
Outdoor Unit			
Power Supply/ Via	V/Hz/Ph	230/50/1	415/50/3
Fan Motor Type	AC	AC	AC
Condensor Type-Rows	nos.	Copper/ 2.5	Copper/ 2
Compressor Type	Twin Rotary	Twin Rotary	Scroll
Noise Level (H/L)	dbA	64	65
Refrigerant Type/Charge	kg	R-32/ 1.76	R-32/ 2.25
Ambient Oper. Range	°C	Up to 48	Up to 48
Unit Dimensions (WxDxH)	mm	928x328x755	1032x383x872
Net/ Gross Weight	kg	58/ 64	80/ 84
Piping Conn.: Liquid	in	3/8"	3/8"
Piping Conn.: Gas	in	5/8"	5/8"
Max Refrigerant Pipe (L)	m	30	30
Max Elevation Difference	m	15	15
Premium Features			
Indoor Unit Display Type	Digital	Digital	Digital
Airflow Control Type	4 Way	4 Way	4 Way
Remote Control	Wireless Backlit LED	Wireless Backlit LED	Wireless Backlit LED
Evaporator Protection	Blue-tec	Blue-tec	Gold-tec
Condensor Protection	Blue-tec	Blue-tec	Blue-tec
Express Cool 52°C	-	-	Yes
Auto Smart Check	-	-	Yes
HD Dust Filter	Yes	Yes	Yes
Auto Blow-n-Clean	Yes	Yes	Yes
Auto Restart	Yes	Yes	Yes
Timer Mode	Yes	Yes	Yes
Easy Serviceability/ Installation			
Wall Support	Provision for support from wall to avoid toppling		
4 Side Field Pipe Connection	Back, Left, Right & Underneath		
Filter removable	Detach filter without removing Intake Grill		

**Under Standard Test conditions. As part of continuous research and development at Cruise, the above features & specifications, model may change without prior notice. Product images shown are for reference only, actual features may vary.



All Cruise products can be recycled. Call 1800 103 6328 to register your request.