



## VARIOQOOL 1S

The VarioQool 1S air conditioner with its Armani gold halo exudes superiority. Equipped with 2-Way Auto Airflow, a 7-stage air purification system and Cruise's 5th gen Tropical Inverter technology - it is engineered to keep your environment fresh, cool and comfortable all day long. Blue-tec fins with Rust-O-Shield protection ensures rust-free performance for years to come.



### THE PREMIER RANGE

#### VarioQool Inverter Series

For maximum efficiency, you need a good night's sleep. And for the best sleep, you need an efficient air conditioner that cools your surroundings equally, maintains absolute silence and so that you don't lose sleep over electricity bills, also saves power.

### VARIOQOOL™

The 5th-gen VarioQool technology features a Tropical-X Rotary compressor and full BLDC motor technology with enhanced airflow efficiency that offers ultra quiet performance for the perfect sleep.

### INVERTER™

AI 4-in-1 convertible cooling that adjusts cooling capacity as per the ambient room conditions for 25% faster cooling and upto 40% energy savings (in eco mode) versus conventional ACs.

SPLIT INVERTER SERIES  
**VARIOOOL 1S**



**THE CEO'S CHOICE.**

Designed to adorn the walls of high-class living spaces for precise climate control, so that you can concentrate on pushing the limits.



**SMART MODES**

This remote features a 2-way Auto swing and Convertible large display modes for faster cooling.



**HD OUTDOOR UNIT**

Boasts a 100% copper condenser with Blue-tec anti-rust protection.

MODEL		CWCVBH-VQ1S123	CWCVBH-VQ1S183	CWCVBF-VQ1S243	CWCVBL-VQ1S243
BEE Star Rating		3	3	3	3
Cooling Capacity	Ton	1.0	1.5	2.0	2.0
(100% / 50% Load)	W	3500/ 1800	5150/ 2575	6250/ 3125	6100/ 3050
Convertible Capacity (H/L)	W	1800/ 3500	2575/ 5150	3125/ 6250	3050/ 6100
Power Consumption	W	1070/475	1570/625	2070/770	1934/710
Current Input	A	4.9	7.2	8.5	8.8/ 5.1
ISEER	W/W	3.80	3.98	3.80	4.00
<b>INDOOR UNIT</b>					
Panel/ Strip Colour		White	White	White	White
Airflow Volume (H/L)	m3/h	780	1050	1150	1050
Fan Speed (H/L)	rpm	1050/ 950	1050/ 950	1050/ 950	1100/ 950
Noise Level (H/L)	dB (A)	49/ 43	46/ 40	49/ 43	46/ 44
Net Dimensions (WxDxH)	mm	1000X295X230	1000X295X230	1000X295X230	1000X295X230
Gross Weight	kg	14.0	14.0	14.0	13.0
<b>OUTDOOR UNIT</b>					
Compressor/ Condensor	type	Inverter/ Copper	Inverter/ Copper	Inverter/ Copper	Inverter/ Copper
Refrigerant Type/ Charge	type	R32	R32	R32	R32
Net Dimensions (WxDxH)	mm	925X605X395	781x557x281	781x557x281	780x557x281
Gross Weight	kg	35	28	35	31.5
Piping Conx: Liquid/ Gas	Dia	φ17.7/ φ6.35	φ12.7/ φ6.35	φ12.7/ φ6.35	φ12.7/ φ6.35
Ambient Operating Range	°C	48	48	48	48
<b>PREMIUM FEATURES</b>					
Indoor Unit Display Type		Magic LED	Magic LED	Magic LED	Magic LED
Airflow Control Type		2 Way Auto	2 Way Auto	2 Way Auto	2 Way Auto
Remote Control		Wireless LED	Wireless LED	Wireless LED	Wireless LED
BLDC Technology		Yes (IDU)	Yes (IDU)	Yes (IDU)	Yes (IDU)
Electronic EEV		-	-	Yes	Yes
Evaporator Protection		Blue-tec	Blue-tec	Blue-tec	Blue-tec
Condenser Protection		Blue-tec	Blue-tec	Blue-tec	Blue-tec
Rust-O-Shield Protection		Yes (IDU side)	Yes (IDU side)	Yes (IDU side)	Yes (IDU side)
Express Cool 50°C		Yes	Yes	Yes	Yes
7 Stage Air Purification		Yes	Yes	Yes	Yes
PM2.5 Filter		Yes	Yes	Yes	Yes
HD Dust Filter		Yes	Yes	Yes	Yes
Auto Blow-n-Clean		Yes	Yes	Yes	Yes

TONNAGE CLASS	1.0	1.5	2.0
STAR RATING	3☆	3☆	3☆

**LUXURY FEATURES**

<p><b>SUPER CONVERTIBLE</b></p> <p><b>4in1</b></p> <p>COOLING</p>	<p><b>LIFETIME WARRANTY</b></p> <p><b>10</b></p> <p>YEAR</p> <p>COMPRESSOR*</p>
<p><b>ANTI-VIRUS+ PROTECTION</b></p> <p>AIR PURIFICATION</p>	<p><b>2D</b></p> <p>AUTO SWING</p>
<p><b>40' FT</b></p> <p>LONG AIRFLOW*</p>	<p><b>EXPRESS COOLING IN</b></p> <p><b>50°C</b></p> <p>AMBIENT</p>
<p><b>ANTI CORROSION</b></p> <p><b>RUST-O SHIELD</b></p> <p>BLUE COATING</p>	<p><b>ULTRA DURABILITY</b></p> <p><b>100%</b></p> <p>COPPER TUBES</p>

\*Under standard test conditions. As part of continuous research and development at Cruise, the above features, specifications and models may change without prior notice. Product images shown are for reference only. Actual features may vary. #Area of cooling is subject to outdoor ambient temperature of 35°C and calculated for residential purposes only.