



THE PREMIER RANGE

VarioQool Inverter Series

For maximum efficiency, you need a good night's sleep. And for the best sleep, you need an efficient air conditioner that cools your surroundings equally, maintains absolute silence and so that you don't lose sleep over electricity bills, also saves power.

Vario QOOL™

The 5th-gen VarioQool technology features a Tropical-X Rotary compressor and full BLDC motor technology with enhanced airflow efficiency that offers ultra quiet performance for the perfect sleep.



AI 4-in-1 convertible cooling that adjusts cooling capacity as per the ambient room conditions for 25% faster cooling and upto 40% energy savings (in eco mode) versus conventional ACs.



SPLIT INVERTER SERIES

VARIOQOOL 1S



THE CEO'S CHOICE.

Designed to adorn the walls of high-class living spaces for precise climate control, so that you can concentrate on pushing the limits.



SMART MODES

This remote features a 2-way Auto swing and Convertible large display modes for faster cooling.



HD OUTDOOR UNIT

Boasts a 100% copper condenser with Bluetec anti-rust protection.

MODEL		CWCVBH-VQ1S123	CWCVBL-VQ1S123P	CWCVBH-VQ1S183	CWCVBM-VQ1S24
BEE Star Rating		3	3	3	3
Cooling Capacity	Ton	1.0	1.0	1.5	2.0
(100% / 50% Load)	W	3500/ 1800	3480/ 1740	5150/ 2575	6100/3050
Convertible Capacity (H/L)	W	1800/ 3500	1740/ 3480	2575/ 5150	3050/6100
Power Consumption	W	1070/475	1117/418	1570/625	1970/730
Current Input	Α	4.9	5.1	7.2	9.0/ 5.3
ISEER	W/W	3.80	3.91	3.98	3.90
INDOOR UNIT					
Panel/ Strip Colour		White	White	White	White
Airflow Volume (H/L)	m3/h	780	800	1050	1050
Fan Speed (H/L)	rpm	1050/ 950	1050/ 950	1050/950	1100/950
Noise Level (H/L)	dB (A)	49/ 43	40/ 36	46/40	46/ 44
Net Dimensions (WxDxH)	mm	1000X295X230	800X292X222	1000X295X230	1000X295X230
Gross Weight	kg	14.0	11.0	14.0	13.0
OUTDOOR UNIT					
Compressor/ Condensor	type	Inverter/ Copper	Inverter/ Copper	Inverter/ Copper	Inverter/ Copper
Refrigerant Type/ Charge	type	R32	R32	R32	R32
Net Dimensions (WxDxH)	mm	925X605X395	672x520x241	781x557x281	780x557x281
Gross Weight	kg	35.0	24.0	28.0	35.0
Piping Conx: Liquid/ Gas	Dia	φ17.7/ φ6.35	φ12.7/ φ6.35	φ12.7/ φ6.35	φ12.7/ φ6.35
Ambient Operating Range	°C	48	48	48	48
PREMIUM FEATURES					
Indoor Unit Display Type		Magic LED	Magic LED	Magic LED	Magic LED
Airflow Control Type		2 Way Auto	2 Way Auto	2 Way Auto	2 Way Auto
Remote Control		Wireless LED	Wireless LED	Wireless LED	Wireless LED
BLDC Technology		Yes (IDU)	Yes (IDU)	Yes (IDU)	Yes (IDU)
Electronic EEV		-	_	-	Yes
Evaporator Protection		Blue-tec	Blue-tec	Blue-tec	Blue-tec
Condenser Protection		Blue-tec	Blue-tec	Blue-tec	Blue-tec
Rust-O-Shield Protection		Yes (IDU side)	Yes (IDU side)	Yes (IDU side)	Yes (IDU side)
Express Cool 50°C		Yes	Yes	Yes	Yes
7 Stage Air Purification		Yes	Yes	Yes	Yes
PM2.5 Filter		Yes	Yes	Yes	Yes
HD Dust Filter		Yes	Yes	Yes	Yes
Auto Blow-n-Clean		Yes	Yes	Yes	Yes

TONNAGE CLASS	1.0	1.5	2.0
STAR RATING	3☆	3☆	3☆

LUXURY FEATURES















